


Product data sheet

SRT-SYSTEM IP20-SRGCT PP/2250 LED - GERÄTETRÄGER FIX CENTRAL.LINE.OPTIC | DEVICE MOUNT FIX CENTRAL.LINE..
21000 830 DALI2 VW RAL 9016 (SRT+19520026260)
REGIOLUX



SRT-Quick-fit mounting system, Device mount, Modullänge/2250. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Housing colour traffic white RAL 9016; Performance level: Powerful Performance (PP) - Powerful, universal all-rounder, sets very high standards for efficiency, service life and warranty period, Light distribution direct, narrow distribution by means of Central.Line.Optic of PMMA plastic, The lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 2299mm x 55mm x 37mm Beam angle: 25° (C0) / 80 ° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 3000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 75000h L80/B10 (Tq 30°C), 100000h L80/B50 (Tq 30°C) Nominal luminous flux: 19897lm Luminaire luminous efficiency: 151lm/W Controller: Electronic driver DALI2 (1 pcs.) System output: 132W Energy efficiency class/light source: C Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 30°C) Ambient temperatur: ta -20°C to 30°C Special properties: Ready for IoT UGR lat./long.: 19.4 / 24.6 Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE Warranty period: 7 years Regiolux GmbH Type: SRGCT PP /2250 LED 21000 830 DALI2 vw RAL 9016 Article number: 19520026260 Product deep link: <https://www.regiolux.de/en/article/19520026260> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	131.7 W	CRI	80
Total flux	19897 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	131.7 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 90.63 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 131.7 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White