


Product data sheet

MIRO NIV LED2400-830 M600Q LDO KA
42925961
ZUMTOBEL



Modular LED ceiling-recessed luminaire with opal optic. Total power: 18.8 W, Slave luminaire for DALI control (DALI only) with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 80% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 2460 lm, Luminaire efficacy: 131 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. Light guided via backlit embossed opal optic UGR < 19 to EN 12464:2011; evenly spaced LED light points; LED modules include high reflection 3Dprotect reflector as protective cover to prevent damage from electrostatic discharge, removable outer PMMA diffuser for homogeneous appearance and simple cleaning; luminaire housing made of sheet steel enamelled in white; Luminaire with external electrical connection; installation as height-adjustable luminaire for cut ceiling apertures and modular ceilings with concealed or visible grid system; please order fixing kit separately; Luminaire wired with halogen-free leads; Dimensions: 598 x 598 x 85 mm, weight: 4.8 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18.8 W	CRI	80
Total flux	2460 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	18.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.54 in
Width: 23.54 in
Height: 3.35 in
Weight: 4.8 kg

Design

Color of housing: White

Electric

System power: 18.8 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
Designation labels: CCC, CE, ENEC