Product data sheet

SMART [4] 2M UL 840 ARRAY ON/OFF ST. ALONE


GWS4220GA840 **GEWISS**





Smart [4] UL is the series of indoor LED lighting devices suitable for lighting of industries and sports facilities. Three different sizes available: 1M, 2M and 4M. The body is made of nylon "Halogen-free" loaded with gray fiberglass (RAL7035) with venting and anti-condensation device, aluminum alloy heat dissipation device EN AB 44300. It is equipped with a double optical system that provides a metallic reflector with ARRAY optics and a metallic reflector with PMMA lenses stabilized at the UV, high efficiency, which allow two different light distributions 60° and 90°. The electrical connection will be via 3x16 AWG tear-proof cable coming out of the product via a PG13.5 plastic cable gland UL certified. Industrial reflector is UL certified UL (UL 1598 - CSA C22.2 No. 250.0-18). It is possible to install hanging, wall and projection devices. It is available with three types of Colour Temperature (4000K / 5700K), CRI>80 Colour Rendering Index and ON/OFF power supply.

Light output 1 (integrated)



Lamp type Nominal lamp power Total flux Luminous efficacy

LED 129 W 19800 lm 153 lm/W CCT

CRI

LOR

4000 K 100% Total power 129 W

80

Mounting mode

Pendant

Shape and measurements

Length: 27.56 in Width: 10.00 in Height: 4.45 in

Adjustability

Fixed

Design

Material impression: Plastic Color of housing: Anthracite / graphite, Silver gray Designer: Gewiss

Electric

System power: 129 W Ballast: ECG Controller: Dimmable 1..10V Appliance Class: II

Protection

IP: 66 IK: 08 Designation labels: CE, UL

Other operating numbers

Ambient temperature range: -13...104°F