

Product data sheet

ARC

05-E090-DC-CL

LEDSC4




IP 66

IK 10



LedsC4 Arc 05-E090-DC-CL Recessed wall lighting for outdoor use. For frontal lighting and downlighting. Includes 2 cable outlets to facilitate chain mounting. Structure material: Concrete, Aluminium. Structure finish: Cement. Diffuser material: Glass. Diffuser finish: Sandblasted. UV protection. Warranty: 5 Years. Product net weight (Kg): 3.2 Product length (mm): 300 Product height (mm): 140 Product aperture (mm): 63 Ø of the hole for recessing (mm): 300x140 Class 1. Glow wire test: 960. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. Maximum power of light source: 9W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 5. Hours of life: 50.000h L80B20. UGR: 19.0. Photobiological risk: RG0. Real flux (lm): 404. Real lm/W: 45. Voltage / frequency range: 220-240/50-60Hz. Voltage: 9. Equipment included: Yes. Total power: 9. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	12.6 W	LOR	100%
Lamp flux	404 lm	Total flux	404 lm
Luminous efficacy	32 lm/W	Total power	12.6 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall recessed, Ceiling mounted

Electric

System power: 12.6 W

Shape and measurements

Length: 2.48 in

Protection

Width: 11.81 in

IP: 66

Height: 5.51 in

IK: 10

Adjustability

Fixed