



# Product data sheet

ARC  
05-E090-DC-CL  
LEDSC4



LedsC4 Arc 05-E090-DC-CL Recessed wall lighting for outdoor use. For frontal lighting and downlighting. Includes 2 cable outlets to facilitate chain mounting. Structure material: Concrete, Aluminium. Structure finish: Cement. Diffuser material: Glass. Diffuser finish: Sandblasted. UV protection. Warranty: 5 Years. Product net weight (Kg): 3.2 Product length (mm): 300 Product height (mm): 140 Product aperture (mm): 63 Ø of the hole for recessing (mm): 300x140 Class 1. Glow wire test: 960. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. Maximum power of light source: 9W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 5. Hours of life: 50.000h L80B20. UGR: 19.0. Photobiological risk: RG0. Real flux (lm): 404. Real lm/W: 45. Voltage / frequency range: 220-240/50-60Hz. Voltage: 9. Equipment included: Yes. Total power: 9. Dimmable equipment included: ON-OFF.

## Light output 1



1 x LED

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 12.6 W  | LOR         | 100%   |
| Lamp flux          | 404 lm  | Total flux  | 404 lm |
| Luminous efficacy  | 32 lm/W | Total power | 12.6 W |
| CCT                | 3000 K  |             |        |
| CRI                | 80      |             |        |

## Mounting mode

Wall recessed, Ceiling mounted

## Shape and measurements

Length: 2.48 in

Width: 11.81 in

Height: 5.51 in

## Adjustability

Fixed

## Electric

System power: 12.6 W

Appliance Class: I

## Protection

IP: 66

IK: 10