Product data sheet


SPOT 1.0 316L L [3000K 1X500MA]
PW10125LAI
L&L LUCE&LIGHT



IP 68 IK 08

Projector for outdoor and underwater applications; surface mounted (ceiling, wall, ground, stake), max depth 10 m; body and trim in AISI 316L stainless steel; 1 power LED; max 2W - max 500mA; includes 5 m neoprene cable H05RN-F 2x0,35/0,75 Ø6,3 mm; series connection; total delivered lumens: 88 lm (3000K, 500mA); optics: 10°, 20°, 40°; LED colour: white - 2700K, 3000K, 4000K, 5000K; blue; ingress protection: IP68; impact resistance: IK08; equipped with IPS; operating temperature: -10°C +45°C; Glow wire test: 960°; photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: III; weight 0,48 kg; dimensions Ø30x57mm; dimming using a dimmable power supply unit; accessories: stake WP0100

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2 W	CRI	80
Total flux	85 lm	LOR	100%
Luminous efficacy	42 lm/W	Total power	2 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 1.42 in
Width: 1.04 in
Height: 1.80 in

Adjustability

Free

Electric

System power: 2 W
Appliance Class: III

Protection

IP: 68
IK: 08