

Product data sheet

MARVIK 2 SURFACE FACADE LUMINAIRES


MV-30013-T2-8030

LIGMAN



- Lamp LED - CRI CRI 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and frame - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear - Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible - MARVIK luminaires with uplight and colder than 3000K CCT do not meet the IDA certification requirements

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.2 W	CRI	80
Total flux	1018 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	50%
		Total power	10.2 W

Mounting mode

Wall mounted

Shape and measurements

Height: 7.87 in

Diameter: 6.97 in

Weight: 2.6 kg

Adjustability

Fixed

Electric

System power: 10.2 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 08

Surface temperature: 40°C