



Product data sheet

HALO SURFACE WHITE 1220MM
R48A122-9016C1830H3S
PLANLICHT




LED HO 3000K 62W 5591lm DALI <https://katalog.planlicht.com/en-us/fam-halo/>

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	7.75 W	CRI	80
Total flux	699 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	7.75 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	7.75 W	CRI	80
Total flux	699 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	7.75 W

Light outputs 3..4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	7.75 W	CRI	80
Total flux	699 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	7.75 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	7.75 W	CRI	80
Total flux	699 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	7.75 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	7.75 W	CRI	80
Total flux	699 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	7.75 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	7.75 W	CRI	80
Total flux	699 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	7.75 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	7.75 W	CRI	80
Total flux	699 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	7.75 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 48.03 in

Width: 48.03 in

Height: 2.52 in

Electric

System power: 62 W

Protection

IP: 20

Designation labels: CE

Adjustability

Fixed