


# Product data sheet

RELIANT LED HIGH BAY 23800 LUMENS, AISLE DISTRIBUTION, ACRYLIC  
RRE-2AN2-EXXX-XXN  
DIALIGHT



Reliant LED High Bay 23,800 Lumens 159 Watts 100-277V AC Neutral White, 80CRI Acrylic Lens CE, ENEC EN 55015 IEC 61000-3-3 IEC 61547 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-6 IEC 61000-4-8 IEC 61000-4-11 Aisle Distribution IP66 Scaled IES File

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3783 K |
| Nominal lamp power | 159 W    | CRI         | 80     |
| Total flux         | 23782 lm | LOR         | 100%   |
| Luminous efficacy  | 150 lm/W | Total power | 159 W  |

## Mounting mode

Pendant

## Shape and measurements

Height: 6.57 in  
Diameter: 17.28 in  
Weight: 9.3 kg

## Adjustability

Rotatable, Tilttable

## Electric

System power: 159 W  
Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC  
Appliance Class: I

## Protection

IP: 66  
IK: 05

## Other operating numbers

Ambient temperature range: -40...149°F