

Product data sheet

FLAT POLYMERO
311921.002.2
RZB




IP
40

IK
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic (polycarbonate). Diffuser fastening: push lock. Available Colours: white Type of Installation: Pendant Dimensions: D 515, H 150 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 2550lm System power: 24W Beam Angle: 114° Number of fittings B10A: 15 Number of fittings B16A: 25 Number of fittings C10A: 26 Number of fittings C16A: 42 Inrush current: 10A Unified Glare Ratio: 19,1 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2550 lm	LOR	100%
Luminous efficacy	106 lm/W	ULOR	9%
		Total power	24 W

Mounting mode

Pendant

Electric

System power: 24 W

Shape and measurements

Height: 5.91 in
Diameter: 20.28 in

Protection

IP: 40
IK: 10

Adjustability

Fixed