
Product data sheet

ENTERO RD-S SOFT 93045
28480 9030
DELTA LIGHT




Luminaire, ceiling recessed (indoor use) from Deltalight, named ENTERO RD-S SOFT 93045, available in the colour(s): black, full white, gold coloured. For recessed mounting, a round opening with a diameter of 76 mm is needed and a min. depth for recessing of 100 mm. This luminaire is equipped with LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm with an optional driver, suitable for currents of 500mA. Light distributor: reflector 45°.

Light output 1




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		




1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		



1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		



1 x LED

Nominal lamp power	10.2 W	LOR	73%
Lamp flux	1038 lm	Total flux	755 lm
Luminous efficacy	102 lm/W	Total power	10.2 W
CCT	1800 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.08 in

Diameter: 3.31 in

Weight: 0.235 kg

Electric

System power: 10.2 W

Appliance Class: II

Protection

IP: 20

Designation labels: CE