Product data sheet


ATENA LINE V3 LED 22000 OPTICS-WIDE E IP65 04 840
19.4215.2521.04
LUXIONA



IP 65 IK 08

Indoor and outdoor luminaire. Assembly: mounted on poles; directly mounted to ceiling construction or surface mounted on slings. The body material is aluminum. Colour - RAL 9005 (black). Dimensions: 1133 x 136 x 126 mm. Weight 4,9 kg. Diffuser: OPTICS (optical system based on lenses). The efficiency of the optical system is 95,17%. Beam angle: (C0-C180) / (C90-C270) - 83,6° / 84,8°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 102000 h L80/B10. Luminaire luminous flux: 21986 lm. Power of luminaire: 122,6 W. Luminaire's light efficiency: 179,3 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,98. Circuit load capacity: 14 (B10), 22 (B16), 14 (C10), 22 (C16). Operating temperature range: -25 ÷ 40° C. Protection degree: IP65. Impact resistant: IK08. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG1.

Light output 1



3 x LED

Nominal lamp power	40.867 W	LOR	52%
Lamp flux	7701 lm	Total flux	12114 lm
Luminous efficacy	188 lm/W	Total power	122.6 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.61 in
Width: 5.35 in
Height: 4.96 in

Adjustability

Tiltable

Design

Color of housing: Black

Electric

System power: 122.6 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -13...104°F