


# Product data sheet

3503.1 LED CG-S WHITE  
40071352901  
EATON EMERGENCY LIGHTING




• Safety luminaire with LED technology for recessed mounting with round bezel • Typical ceiling cut-out diameter of 68 mm and low profile of only 30 mm • Compact housing for LED supply (required height for entering the ceiling only 100 mm) including through-wiring clamp and strain relief • Wide light point spacing due to wide light distribution optics and high power LEDs •Up to 18 m from luminaire to luminaire for escape route illumination and wide area illumination (3x03.1) •Up to 20 m from luminaire to luminaire for escape route illumination and wide area illumination (3x04.1)

## Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	4.4 W	CRI	65
Total flux	470 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	4.4 W

## Light output 2 (integrated, emergency)



Lamp type	LED	CCT	6000 K
Nominal lamp power	4.4 W	CRI	65
Total flux	470 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	4.4 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 0.08 in  
Diameter: 3.15 in

## Adjustability

Fixed

## Electric

System power: 8.8 W  
Appliance Class: II

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency power supply: Central battery feed-in  
Emergency sign: N/A

## Protection

IP: 20

IK: 03