

Product data sheet

CATENARY SUSPENDED LUMIN. AVILA 4000K
10.10530.0VXXX
HESS




IP
65

Round luminaire canopy made of aluminium. Holder device for on-site suspension cable. With ball joint for alignment of the luminaire.
Cylindrical luminaire enclosure made of PMMA, satin look in the upper part. Diameter 300mm.


Light output 1




1 x LED			
Nominal lamp power	37 W	LOR	100%
Lamp flux	5506 lm	Total flux	5506 lm
Luminous efficacy	149 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	37 W	LOR	100%
Lamp flux	5492 lm	Total flux	5492 lm
Luminous efficacy	148 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		




1 x LED			
Nominal lamp power	27 W	LOR	100%
Lamp flux	2926 lm	Total flux	2926 lm
Luminous efficacy	108 lm/W	Total power	27 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2863 lm	Total flux	2863 lm
Luminous efficacy	106 lm/W	Total power	27 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2943 lm	Total flux	2943 lm
Luminous efficacy	109 lm/W	Total power	27 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	3984 lm	Total flux	3984 lm
Luminous efficacy	108 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	4096 lm	Total flux	4096 lm
Luminous efficacy	111 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	5585 lm	Total flux	5585 lm
Luminous efficacy	105 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	7426 lm	Total flux	7426 lm
Luminous efficacy	140 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	5463 lm	Total flux	5463 lm
Luminous efficacy	103 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	7322 lm	Total flux	7322 lm
Luminous efficacy	138 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	5616 lm	Total flux	5616 lm
Luminous efficacy	106 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	7303 lm	Total flux	7303 lm
Luminous efficacy	138 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	37 W	LOR	100%
Lamp flux	4073 lm	Total flux	4073 lm
Luminous efficacy	110 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	37 W	LOR	100%
Lamp flux	5584 lm	Total flux	5584 lm
Luminous efficacy	151 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 16.44 in

Width: 1.97 in

Height: 3.49 in

Adjustability

Rotatable

Electric

System power: 27-53 W

Protection

IP: 65