
Product data sheet

FLEXBAR DIFFUSER - 15 W - OPAL - SUSPENDED - CONTINUOUS - CORNER - SECONDARY LEFT HAND - UPLIGHT
FD15CSLUO


THORLUX LIGHTING



IP 20

Slimline linear luminaires. Elegant linear luminaire ideal for a wide range of applications. The uninterrupted diffuser creates striking lines of light across the ceiling, whether mounted on the surface, suspended, or recessed. The range includes individual, continuous, and corner lengths to allow designers to be flexible with their lighting designs. The dropped diffuser, available in opal and low-glare, provides upward light, creating a softer appearance whilst supporting illumination on the walls and ceiling, and aiding compliance to EN 12464-1 and LG7. Applications: offices, education, meeting rooms, healthcare, circulation, leisure, and retail.


Light output 1



1 x LED

Nominal lamp power	8 W	LOR	100%
Lamp flux	1128 lm	ULOR	9%
Luminous efficacy	141 lm/W	Total flux	1128 lm
CCT	4000 K	Total power	9 W
CRI	80		

Light output 2



1 x LED

Nominal lamp power	7 W	LOR	100%
Lamp flux	1102 lm	ULOR	9%
Luminous efficacy	157 lm/W	Total flux	1102 lm
CCT	4000 K	Total power	8 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 34.25 in
Width: 1.73 in
Height: 2.68 in

Adjustability

Fixed

Electric

System power: 17 W

Protection

IP: 20