


Product data sheet

VIGILANT LED LOW BAY 4000 LUMENS, ULTRA WIDE DISTRIBUTION, DIFFUSED POLYCARBONATE DOME LENS
LEXLUC24XXXXXN
DIALIGHT



Vigilant LED Low Bay 4,000 Lumens 42 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Diffused Polycarbonate Dome Lens UL 1598/A (wet locations) CSA C22.2 No. 250 NEMA 4X CE, ENEC EN 60598:2015 EN60598-2-1 (ed.1), IEC 60598-2-1 (ed.8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN62493:2010 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-2 IK10 Ultra Wide Distribution IP66/67 LM79 Tested IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	38.6 W	CRI	80
Total flux	3922 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	38.6 W

Mounting mode

Pendant

Shape and measurements

Length: 15.94 in
Width: 15.94 in
Height: 8.27 in

Adjustability

Rotatable, Tilttable

Electric

System power: 38.6 W
Appliance Class: I

Protection

IP: 66
IK: 10

Other operating numbers

Ambient temperature range: -40...149°F