Product data sheet

X-LINE SLIGHT SPOTS L-DOWN LED 2600 MICRO-PRM EDD / 2X 600 15° EDD 24 830 / L-1162MM S-1,5M TWO CIRCUIT
19.4398.211F.24


LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - anodised aluminum. Dimensions: 1162 x 34 x 68 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA) / optical system based on PMMA lenses. The efficiency of the optical system is 81,50%. Beam angle: (C0-C180) / (C90-C270) - 86,2° / 111° // (C0-C180) / (C90-C270) - 17,8° / 19,8°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 2288 / 1020 lm. Power of luminaire: 15,5 / 10,8 W. Luminaire's light efficiency: 147,6 / 94,4 lm/W. Driver: DIM DALI (EDD) / DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Circuit load capacity: 8 (B10), 14 (B16), 13 (C10), 20 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



2 x LED

Nominal lamp power	7.75 W	LOR	52%
Lamp flux	1404 lm	Total flux	1472 lm
Luminous efficacy	181 lm/W	Total power	15.5 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 45.75 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 15.5 W
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F