


Product data sheet

FLOODLIGHT
V1-I0-701X3-04D19-6521050 AIRQUB 210 W 210W 5000K DALI 20°
VARTON




IP
67

IK
01

High-power floodlight with a wide range of wattage and optics. Best lumens/mass/size ratio in its class of solutions. Material: Cast aluminum radiator, steel body parts, acrylic optic. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 135° in 5° increment. The luminaire has a wire for connecting to the mains. Wire length 1 meter. Application: Outdoor areas. Industrial facilities. High-mast lighting. Input voltage (AC, 50Hz), V: 90...305 AC frequency, Hz: 50 Input voltage (DC), V: 127...300 Flicker, %: 5 Climatic modification and category of placement: YXL11 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK01 Power factor: 0,95
<https://www.varton.ru/products/prozhektory/airqub/airqub-210-vt/svetodiodnyy-prozhektor-varton-airqub-210-vt-5000-k-20-dali/>

Light output 1



1 x LED			
Nominal lamp power	210 W	LOR	100%
Lamp flux	32250 lm	Total flux	32334 lm
Luminous efficacy	154 lm/W	Total power	210 W
CCT	5000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 21.26 in
Width: 11.02 in
Height: 10.83 in

Adjustability

Fixed

Electric

System power: 210 W

Protection

IP: 67
IK: 01