


Product data sheet

APOLLO G2 1560MM PO 2X86W 060° 25000LM
94300B5N
PRACHT



New generation of the proven APOLLO damp-proof reflector luminaire. Elegant socket end pieces made of newly designed PBT. Easy one-man installation of the reflector through integrated plug-in device with directional guides and captive, easy-to-close clips made of stainless steel. All-round closed housing made of white, glass fiber reinforced, flame-retardant, largely acid and alkali-resistant polyester resin, protection class IP65. Reflector swivels 120°, with practical locking in 10° steps. Short, aging-resistant silicone seals. Integrated electronic converter. Particularly robust due to thermal decoupling of LED and converter. Through-wiring up to max. 5x2.5mm² + 2x1.5mm² possible. The permissible ambient temperature decreases by 1°C for every 2A load of the through-wiring. Variable mounting distances through PRACHT-CLAMP-SYSTEM made of stainless steel, suitable for ceiling and horizontal wall mounting, pendant and rail mounting with accessories possible.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	172 W	CRI	80
Total flux	25000 lm	LOR	100%
Luminous efficacy	145 lm/W	ULOR	2%
		Total power	172 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.42 in
Width: 9.13 in
Height: 5.59 in
Weight: 4.7 kg

Adjustability

Tiltable

Electric

System power: 172 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -4...104°F