Product data sheet


LIGHTSTREAM MIDI II
722288.114
RZB



IP 66 IK 08

Series: LIGHTSTREAM midi Clever combination of spotlight and pole luminaire in one. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Tilt angle can be adjusted and locked in 5 degree steps featuring angular scale. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass, edge printed. Cover screwed to housing. Lens system made of plastic (PMMA). Replaceable LED spot modules according to ZHAGA standards. Asymmetrical narrow beam light distribution for area lighting (e.g. parking lots, loading zones) Constant light output (CLO). With NFC programming interface. Pre-assembled connection cable, length 8 m. Modular design: Mounting module must be ordered separately. Colour: silver, matt (approx. RAL 9006) Length: 516 mm Width: 220 mm Height: 56 mm Lamp: LED System power: 93 W Rated luminous flux: 12300 lm Luminous efficiency: 132 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 66

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	93 W	CRI	70
Total flux	12300 lm	LOR	28%
Luminous efficacy	132 lm/W	ULOR	8%
		Total power	93 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 8.66 in
Width: 20.31 in
Height: 2.20 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 93 W

Protection

IP: 66
IK: 08