

Product data sheet

VANCOUVER 5 LIGHT COLUMNS


VA-20021-W-W40

LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Maximum wind load resistance is 160 km/h - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.5 W	CRI	80
Total flux	1336 lm	LOR	100%
Luminous efficacy	34 lm/W	Total power	39.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	20.7 W	CRI	80
Total flux	1683 lm	LOR	100%
Luminous efficacy	81 lm/W	Total power	20.7 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 157.48 in

Diameter: 6.30 in

Weight: 52.4 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 60.2 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C