


Product data sheet


HONEYCOMB GRATING 34W 1200MM 4000K CRI80
LS40HP
COLORS



IP
20

1.The 40mm light-emitting surface luminaire; 2.Supports various installation methods including suspension, ceiling mounting, and embedded with edge, catering to different spatial installation needs; 3.Supports direct illumination, as well as direct and indirect lighting requirements; 4.Offers 7 professional optical options to meet diverse lighting scene applications (diffusion, prism, honeycomb, louvers, grille, single bias, double bias); 5.High luminous efficacy (130LM/W), low glare (UGR < 19), with three-level color temperature adjustment and multiple versions available for enhanced functionality; 6.Provides 180 minutes of emergency lighting for power outages; 7.Features multiple intelligent control systems such as NO/OFF, 1-10V, DALI-2, CASAMBI control, making lighting more intelligent and convenient;

Light output 1



1 x LED			
Nominal lamp power	34 W	LOR	100%
Lamp flux	2550 lm	Total flux	2550 lm
Luminous efficacy	75 lm/W	Total power	34 W
CCT	3991 K		
CRI	81		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 47.24 in

Width: 1.57 in

Height: 3.27 in

Adjustability

Fixed

Electric

System power: 34 W

Protection

IP: 20