


Product data sheet

RKSK 260/1300-840 HPC
1420061
RIDI



Diffuser luminaire RKSK Design: Round single diffuser luminaire, with LED modules for ceiling and wall installation. Round luminaire fitting made of polycarbonate, in white. Two cable entries and four holes for fastening into the fitting. Factory-fitted equalising membrane in the housing, spring clips for fixing the diffuser into position. Equipped with RIDI-LED modules. LED modules made of circular segments mounted on the bottom of the luminaire for standardised illumination of the luminaire cover. LED modules with copper coating on both sides for optimal heat distribution. Colour rendering in index Ra \geq 80, colour temperature 3000 Kelvin (830), 4000 Kelvin (840), other colour temperatures possible on request. Colour rendering in index Ra \geq 80, colour temperature 3000 Kelvin (830), 4000 Kelvin (840), other colour temperatures possible on request. Electronic converter for LED, 220-240 Volt, 0/50-60 Hz and internal connector block 5x2.5mm². Mounting: Direct ceiling/wall mounting without additional accessories. RKSK 260/... HPC Semi-circular diffuser made of opal UV-stabilised polycarbonate (PC), Diameter 290 mm. Smooth diffuser surface.

Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	76%
Lamp flux	1560 lm	ULOR	13%
Luminous efficacy	118 lm/W	Total flux	1183 lm
CCT	4000 K	Total power	10 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 12.71 in
Width: 11.50 in
Height: 4.92 in

Adjustability

Fixed

Electric

System power: 10 W
Appliance Class: I

Protection

IP: 65
IK: 10