
Product data sheet


LED DOWNLIGHTS
V1-R0-70135-20D01-2001240 DL-ROLL OPAL Ø90 SURFACE MOUNTED 12W 4000K DALI
VARTON



IP 20 IK 01

Impact resistance: IK01 Power factor: 0,95 Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Protection class: II Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP20 https://www.varton.ru/products/daunlayty/dl-roll/dl-roll-opal-90-nakladnye/svetodiodnyy-svetilnik-varton-dl-roll-12-vt-nakladnoy-4000-k-90kh170-mm-ral7045-seryy-muar-s-rasseiv_1/

Light output 1



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	1100 lm	Total flux	1100 lm
Luminous efficacy	92 lm/W	Total power	12 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.69 in
Diameter: 3.54 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 20
IK: 01