Product data sheet


ARCHITECTURAL LIGHTING
V1-G1-92444-04L03-6600940 FRIEZE 2.0 XS 9W 4000K 45°
VARTON



IP 66 IK 08

Frieze 2.0 XS is an ultra—compact spotlight with high luminous efficiency for delicate architectural illumination. Its small dimensions make it an ideal solution for installation in hard-to-reach places: between windows, on canopies, ledges and thin decorative elements of the facade. Perfect light uniformity is achieved through the use of high-quality SEOUL Z5M4/Z5M2 LEDs, selected by color temperature within three Macadam steps (3 SDCM), as well as a wide range of optics that accurately adapt the luminous flux to any task. Protection class: I Ingress protection (IP): IP66 Impact resistance: IK08 https://www.varton.ru/products/arkhitekturnoe-osveshchenie/frieze-2-0-xs/frieze-2-0-xs_1/svetilnik-varton-arkhitekturnyy-frieze-2-0-xs-9-vt-linzovannyy-45-4000-k-ral9005-chernyy-muar/

Light output 1



1 x LED

Nominal lamp power	9 W	LOR	100%
Lamp flux	1035 lm	Total flux	1035 lm
Luminous efficacy	115 lm/W	Total power	9 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.69 in
Width: 4.69 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 9 W

Protection

IP: 66
IK: 08