Product data sheet


LUNA CROSS
6009-0-3-421-XX
UNILAMP



IP 65 IK 06

Description LUNA is a recessed luminaires utilizing LED light sources. The glare-free cover version enables LUNA to be installed in situations where comfortable low-level illumination is a requirement. LUNA is available in 4 different front covers. They have a shallow housing and can be installed in either wall or step that have limited recessing depth. The high quality LED driver is integrated inside the luminaire for ease of installation. Luna is widely used to illuminate stairways, pathways and walls where a general or directional light is needed Spec • Designed, Manufactered and tested according to IEC 60598-1, IEC 60598-2-1, IEC 60598-2-2 and VDE regulations. • LM6 die-cast aluminium body. • GFR polymer recess box. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 terminal block. • Weather proof grommet. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	10 W	Socket	G24D-1
Lamp flux	600 lm	LOR	100%
Luminous efficacy	60 lm/W	ULOR	7%
CCT	3000 K	Total flux	600 lm
CRI	84	Total power	14 W

Mounting mode

Wall recessed

Shape and measurements

Length: 7.13 in
Width: 4.33 in
Height: 7.13 in

Adjustability

Fixed

Electric

System power: 14 W
Appliance Class: I

Protection

IP: 65
IK: 06