Product data sheet

TX-MOVE
901728.004.2.76
RZB



IP 20 IK 04

Series: TX-MOVE Einlege/Einbau-Flächenstrahler. Housing made of sheet steel, powder-coated. Swivel range: 90°. High-efficiency LED units with optimum light control thanks to clear plastic (PC) lens optics. Special microstructures reduce the yellow corona (caused by chromatic aberration). Symmetrical light distribution. Best colour rendering with CRI >90 for fresh products and coloured textiles. Suitable for laying in grid ceiling module 625. Connected converter included in separate gearbox. Suitable for through-wiring. MultiLumen: Luminous flux variable in 3 steps. Accessories: Mounting frame for installation in suspended ceilings. Replaceable components make repairs possible and extend the service life. Colour: silver, matt (approx. RAL 9006) Length: 622 mm Width: 116 mm Height: 39 mm Cut-out length: 602 mm Cut-out width: 98 mm Recess height: 100 mm Lamp: LED Socket: without socket Colour temperature: 2700K Colour rendering index (CRI): 90 System power: 16 W Rated luminous flux: 1950 lm Beam angle Down: 30° Luminous efficiency: 122 lm/W System power 2: 23 W Rated luminous flux 2: 2750 lm Luminous efficiency 2: 120 lm/W System power 3: 31 W Rated luminous flux 3: 3500 lm Luminous efficiency 3: 113 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1



1 x LED

Nominal lamp power	31 W	LOR	67%
Lamp flux	3500 lm	ULOR	14%
Luminous efficacy	75 lm/W	Total flux	2335 lm
CCT	2700 K	Total power	31 W
CRI	92		



1 x LED

Nominal lamp power	23 W	LOR	67%
Lamp flux	2750 lm	ULOR	14%
Luminous efficacy	80 lm/W	Total flux	1834 lm
CCT	2700 K	Total power	23 W
CRI	92		



1 x LED

Nominal lamp power	16 W	LOR	67%
Lamp flux	1950 lm	ULOR	14%
Luminous efficacy	81 lm/W	Total flux	1301 lm
CCT	2700 K	Total power	16 W
CRI	92		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.57 in
Width: 24.49 in
Height: 1.54 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: Silver gray

Electric

System power: 16-31 W

Protection

IP: 20
IK: 04