

Product data sheet


KORA VI (1-ARMED)
9.106.2032.05
LEIPZIGER LEUCHTEN



IP
55

One or double-bracket pole luminaire with intensive brightness (height 4.50 and 6.00 m) in order to illuminate streets and footpaths. - Attachment made of plexiglass XT, sandblasted on one side - Computer-optimized reflector systems for high-pressure lamps with clear glass tubular bulbs/DULUX lamps ensures excellent illumination - Special steel luminaire body and unit carrier, available painted in any RAL or DB colour without surcharge, or ground and passivated - Luminaire case fold out for lamp change - Adapter jack connection - Included pole door to take in a cable joint box - Scope of supply includes square pole, incl. special steel bracket and electrical supply element (intermediate unit, ignition unit, condenser) - Available for 3 fastening variants in the ground: flange sheet, flange sheet in order to pave over, or end piece, situated at the pole, to set in the ground Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	61%
Lamp flux	6600 lm	Total flux	4046 lm
Luminous efficacy	49 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode

Pole integrated

Electric

System power: 83 W

Shape and measurements

Length: 41.73 in

Width: 11.81 in

Height: 3.94 in

Protection

IP: 55