

# Product data sheet

PTECDHO L50 60 E3 & PTECD SSR \* DGR  
PROTEC LED HO EMERGENCY  
DEXTRA




IP  
20




Protec LED High Output - Ø174mm, IP20 Recessed High Output Downlighter with a 60 Degree Lens, ABS housing and bezel, zinc plated spring steel fixing clips and anodised semi specular aluminium reflector and drop glass ring. E3 - Emergency control gear (416 lumens output) - Attachments may reduce emergency lumen output. ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* Replace \* with WH for White or GY for Grey Order the luminaire with trim accessory attachment

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.2 W	CRI	80
Total flux	408 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	4.2 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31.16 W	CRI	80
Total flux	4106 lm	LOR	100%
Luminous efficacy	132 lm/W	Total power	31.16 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 5.12 in  
Diameter: 6.89 in

## Adjustability

Fixed

## Electric

System power: 35.36 W  
Ballast: ECG

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Protection

IP: 20

Designation labels: CE