
Product data sheet

LEDILINE 1200 LM 46W HIGH POWER LED WALL-WASHER LUMINAIRE ; RGB ; NARROW BEAM M485SN962LED1RGB-A


IP 65

MEGALITE




LEDILINE RGB LED surface mount luminaire is Megalite state of the art design suitable for architectural and façade lighting used in outdoor application such as bridges, building facades, pillars and etc. Specially designed lenses results in wide or narrow light distribution. Sturdy body and high ingress protection IP65 are among the highlights of LEDILINE

Light output 1 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	16 W	CRI	-50
Total flux	204 lm	LOR	100%
Luminous efficacy	13 lm/W	Total power	16 W

Light output 2 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	15 W	CRI	-18
Total flux	684 lm	LOR	100%
Luminous efficacy	46 lm/W	Total power	15 W

Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	15 W	CRI	-29
Total flux	312 lm	LOR	100%
Luminous efficacy	21 lm/W	Total power	15 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.36 in Width: 37.99 in Height: 3.15 in

Adjustability

Fixed

Electric

System power: 46 W

Protection

IP: 65