


# Product data sheet

QUANTUM 1 FLOODLIGHTS,PROJECTORS  
QA-50004-N-40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30, 40 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector or PMMA lens - Clear toughened glass - Integral control gear

## Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	9.2 W	CRI	80
Total flux	608 lm	LOR	100%
Luminous efficacy	66 lm/W	Total power	9.2 W

## Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	9.2 W	CRI	-50
Total flux	88 lm	LOR	100%
Luminous efficacy	10 lm/W	Total power	9.2 W

## Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	9.3 W	CRI	-18
Total flux	596 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	9.3 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	6.9 W	CRI	-29
Total flux	342 lm	LOR	100%
Luminous efficacy	50 lm/W	Total power	6.9 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 12.13 in  
Diameter: 7.09 in  
Weight: 3.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 34.6 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

Protection

IP: 66  
IK: 08  
Surface temperature: 40°C