
Product data sheet


ETV130 [LE/IW] IP67:LED-48/30W/4K
186-0399
WE-EF



IP 67 IK 08

IP67, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable. Linear PMMA LED lens. Factory installed LED circuit board. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DALI interface in thermally-separated compartment. Electronic converter with DALI interface The optional installation blockout is recommended for mounting. To be ordered separately.

Light output 1



48 x LED

Nominal lamp power	0.625 W	LOR	70%
Lamp flux	90 lm	Total flux	3016 lm
Luminous efficacy	90 lm/W	Total power	33.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Length: 36.50 in
Width: 1.89 in
Height: 2.13 in
Weight: 6 kg

Electric

System power: 33.5 W
Appliance Class: I

Protection

IP: 67
IK: 08