


Product data sheet

ILLUMINATING BOLLARD NOVARA L SINGLE 1800K
12.7261X.0VXXX
HESS




Triangular luminaire body made of cast aluminium. Luminaire enclosure made of single-pane safety glass. Cylindrical bollard made of steel, galvanised, optionally with embedded base or flange plate. Inclination of the luminaire body infinitely adjustable. Bracket made of cast aluminium. Cable protection hose made of stainless steel mesh.


Light output 1




| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 10 W | LOR | 100% |
| Lamp flux | 696 lm | Total flux | 696 lm |
| Luminous efficacy | 70 lm/W | Total power | 10 W |
| CCT | 1800 K | | |
| CRI | 80 | | |



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 10 W | LOR | 100% |
| Lamp flux | 580 lm | Total flux | 580 lm |
| Luminous efficacy | 58 lm/W | Total power | 10 W |
| CCT | 1800 K | | |
| CRI | 80 | | |



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 10 W | LOR | 100% |
| Lamp flux | 805 lm | Total flux | 805 lm |
| Luminous efficacy | 80 lm/W | Total power | 10 W |
| CCT | 1800 K | | |
| CRI | 40 | | |


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

10 W
1028 lm
103 lm/W
1800 K
40

LOR
Total flux
Total power

100%
1028 lm
10 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

10 W
691 lm
69 lm/W
1800 K
80

LOR
Total flux
Total power

100%
691 lm
10 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

6 W
417 lm
70 lm/W
1800 K
80

LOR
Total flux
Total power

100%
417 lm
6 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

6 W
344 lm
57 lm/W
1800 K
80

LOR
Total flux
Total power

100%
344 lm
6 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI


6 W
531 lm
88 lm/W
1800 K
80

LOR
Total flux
Total power

100%
531 lm
6 W



| | | | |
|--------------------|----------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 6 W | LOR | 100% |
| Lamp flux | 678 lm | Total flux | 678 lm |
| Luminous efficacy | 113 lm/W | Total power | 6 W |
| CCT | 1800 K | | |
| CRI | 80 | | |



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 6 W | LOR | 100% |
| Lamp flux | 414 lm | Total flux | 414 lm |
| Luminous efficacy | 69 lm/W | Total power | 6 W |
| CCT | 1800 K | | |
| CRI | 80 | | |

Mounting mode

Standing / Bollard

Shape and measurements

Length: 7.32 in

Width: 11.02 in

Height: 38.41 in

Adjustability

Tiltable

Electric

System power: 6-10 W

Protection

IP: 65