Product data sheet


FLINDT WALL Ø400 LED 2700K 20W, WHT TEXT
5747402209
LOUIS POULSEN



IP 65 IK 09

Flindt Wall Design by: Christian Flindt Koncept: The fixture emits an asymmetrical non glary, downward directed light distribution. Softly illuminating its cut-out shape while providing an efficient horisontal illumination on the ground or floor. Perfectly fit for indoor as well as outdoor applications. Finish: Aluminium, Corten, White, or Black coloured. Textured surface, powder coated. Materials: Front and back housing: Die casted. Light Engine: Die casted aluminum and injection molded acrylic. Mounting: Ø200 : Installation cable 3x1.5mm2 . Looping not possible - Integrated driver. Ø300/400: Installation cable- 3x1.5mm2 + 2x1.5mm2 (Dimming). Looping possible. Integrated driver. Sizes and weights: Width x Height x Length (mm) 60 x 200 x 200 Max 0.9 kg 80 x 300 x 300 Max 3.8 kg 100 x 400 x 400 Max 6.7 kg Class: Ingress protection IP65. Electric shock protection I w. ground. Ø200: IK08. Ø300/400: IK09.

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	20 W	CRI	90
Total flux	1018 lm	LOR	69%
Luminous efficacy	51 lm/W	Total power	20 W

Mounting mode

Wall mounted

Shape and measurements

Length: 15.75 in
Width: 3.94 in
Height: 15.75 in

Adjustability

Fixed

Electric

System power: 20 W
Appliance Class: I

Protection

IP: 65
IK: 09