


Product data sheet

INDU Highbay 100W LED Pendel 70GR PC
3530951-70
SOLAR



Indu HighBay LED armatur for høye takhøyder i industri, butikker, lager etc. Erstatte tradisjonelle dampplampearmaturer med kvikksølv, metallhalogen eller høytrykk natrium. Kan leveres med 3 ulike reflektorer. Alu reflektor 3530954 60gr (smal), 3530956 90gr (medium) eller 3530955 70gr prismatisk reflektor i akryl. Armatur: Armaturhus i støpt aluminium. Armaturhus /kjølebuffel i sort. IP65. Montering: Henges i wire/kjede. Armatur leveres med en kraftig øyeskrue/krok som festes på toppen av armaturhuset. Tilkobling: Leveres med 3m gummikabel. Klasse I. Lyskilde: LED modul, RA >80 Fargetemperatur: 4000 K Levetid 50.000 timer L70. Kommer i flere varianter, Lumenverdi: 100W = 12350 lumen 150W = 225000 lumen 240W = 29000 lumen

Light output 1 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	100.8 W	CRI	84
Total flux	12731 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	7%
		Total power	100.8 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 0.04 in

Diameter: 13.39 in

Adjustability

Height adjustable

Electric

System power: 100.8 W

Appliance Class: I

Protection

IP: 23