Product data sheet


DEECOS P MAXI
911540.004.3_982650.002
RZB



IP 20 IK 06

Series: DEECOS P maxi Cylindrical pendant luminaire. Housing made of die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel, with magnetic attachment. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. Transparent suspension cable 2 m, can be shortened. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: silver Diameter: 123 mm Height: 181 mm Suspension length: 2000 mm Lamp: LED Socket: without socket Colour temperature: 3500K Colour rendering index (CRI): 90 System power: 36 W Rated luminous flux: 3850 lm Beam angle Down: 14° Luminous efficiency: 107 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	36 W	CRI	80
Total flux	2250 lm	LOR	67%
Luminous efficacy	62 lm/W	ULOR	14%
		Total power	36 W

Mounting mode

Pendant

Shape and measurements

Height: 7.13 in
Diameter: 4.84 in

Adjustability

Fixed

Electric

System power: 36 W

Protection

IP: 20
IK: 06