## Product data sheet

NORA V (1-ARMED) 9.775.2032.05

LEIPZIGER LEUCHTEN








For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure sodium vapou	r lamp
Name in all laman in autor	70 M

Nominal lamp power	70 W
Lamp flux	5600 lm
Luminous efficacy	51 lm/W
CCT	2000 K
CRI	25

LOR 76%
ULOR 2%
Total flux 4268 lm
Total power 83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 11.81 in Diameter: 21.26 in Electric

System power: 83 W

Protection

IP: 55