

Product data sheet


TRAFFIK LED 35W 4950LM 3000K IP66 O44P - FOR PEDESTRIAN CROSSINGS, RIGHT SIDE TRAFFIC GRAY I
130292.3L141.110

LUG



Professional streetlight luminaire for LED light sources. Mounting: on outriggers $\varnothing 60/48\text{mm}$ Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.033 m^2 . Power: 220-240V 50/60Hz Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection, NTC Other remarks: the pole and boom are not part of the luminaire; luminaire available in protection class I and II Warranty: 5 years Application: local roads, express roads, town roads, residential area roads, area lighting, avenues, promenade, parking areas Type of optics: O44P - for pedestrian crossings, right side traffic

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	70
Total flux	4950 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	35 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 19.88 in

Width: 9.06 in

Height: 3.15 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 35 W

Controller: DALI

Appliance Class: I

Protection

IP: 66

IK: 08