Product data sheet


SATIN2 MRE L650 24L33 A/S RD IO
96267264
THORN LIGHTING



IP 68 IK 10

A discreet floor recessed linear floodlight for façade illumination applications. 24 LEDs driven at 330mA with asymmetrical distribution. Electronic, fixed output control gear. Body: extruded aluminium (EN AW-6060 T6) painted textured silver grey. Sides: die-cast aluminium painted textured silver grey. Enclosure: tempered glass 10mm thick. Class II electrical, IP68, IK08. Pre-wired with 1m of 2x1mm² H05RNF cable at both ends. Complete with red LED Dimensions: 654 x 96 x 112 mm Total power: 20 W Weight: 3.16 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	99
Total flux	758 lm	LOR	100%
Luminous efficacy	38 lm/W	Total power	20 W

Mounting mode

Floor recessed

Shape and measurements

Length: 25.75 in
Width: 3.78 in
Height: 4.41 in
Weight: 3.2 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 20 W
Voltage: 230 V AC
Appliance Class: II

Protection

IP: 68
IK: 10
Designation labels: CE