



Product data sheet

RECESSED CEILING LUMINAIRE PURELITE SLIM D 21W CRI > 80 3000
2004.4879 - PURLTD S CR1219X63 LED2200-830 DALI RUN
REGENT



Recessed ceiling luminaire Purelite Slim D with LED, system power: 21 W, luminous flux of luminaire 2200 lm, standby power 0.5 W, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, diffuser in synthetic material opal, RUN optics, 1 integral control gear, DALI, protection class I, ingress protection IP20, glow wire test 650 °C, impact strength: IK 08, this product contains a light source of energy efficiency class B L = 1219 mm, B = 63 mm, EL = 1212 mm, EB = 54 mm, ET = 35 mm

Light output 1



1 x LED			
Nominal lamp power	15.6 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	141 lm/W	Total power	21 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.99 in

Width: 2.48 in

Height: 1.38 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 21 W

Appliance Class: I

Protection

IP: 20

IK: 08