

Product data sheet

NOTOR 65 INDIRECT 2400 SINGLE WHITE 3K
13506-402
FAGERHULT



Installation Single or continuous installation via wire suspension or surface mounted. Installation via wire suspension requires wire brackets which provide flexible c/c, see accessories. See wire suspension. Can also be wall mounted with special brackets, see Accessories. Connection The luminaire is equipped with an access hole for cabling on the top. The luminaire unit is equipped with a through-wiring cable (5x1.5 mm²) and a snap-in connection in each end-cap. In a continuous installation, the luminaire row should always begin with a start luminaire. Design Luminaire body enameled in white (RAL 9016) or natural anodised, extruded aluminium finish. Dimming CLO (Constant Light Output) and DALI/Phase-pulse control as standard. CLO means that the luminaire provides the same amount of light throughout its service life. Accessories Assembly fittings and supplementary components, see Accessories. Miscellaneous The LEDs are protected against contact. 1200 mm 3.0 kg 2400 mm 6.0 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	43 W	CRI	80
Total flux	5510 lm	LOR	100%
Luminous efficacy	128 lm/W	ULOR	100%
		Total power	43 W

Mounting mode

Pendant

Shape and measurements

Length: 98.62 in
Width: 2.56 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 43 W

Protection

IP: 20