Product data sheet


KUBIK POLE 900 4/2/4/0 LED 1,7W ODB E IP65 22 6500K
19.3161.0088.22
LUXIONA



IP 65 IK 09

Outdoor luminaire. Assembly: for the ground. The body material is aluminum. Colour - RAL 9007 (dark grey, metallic, fine structure). Dimensions: 150 x 150 x 900 mm. Diffuser: transparent polycarbonate. The efficiency of the optical system is 83,44%. Beam angle: asymmetric light distribution. Light source type: LED. Colour of the light 6500 K. CRI>80. Lifetime of LED sources: 50000 h L70/B50. Luminaire luminous flux: 1435 lm. Power of luminaire: 21 W. Luminaire's light efficiency: 68,3 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,5. Circuit load capacity: 20 (B10), 30 (B16), 33 (C10), 53 (C16). Operating temperature range: -25 ÷ 30° C. Protection degree: IP65. Impact resistant: IK09. Protection against electric shock: I.

Light output 1



10 x LED

Nominal lamp power	2.1 W	LOR	52%
Lamp flux	172 lm	Total flux	902 lm
Luminous efficacy	82 lm/W	Total power	21 W
CCT	6500 K		
CRI	80		

Mounting mode

Pole integrated, Standing / Bollard

Shape and measurements

Length: 5.91 in
Width: 5.91 in
Height: 35.43 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 21 W
Appliance Class: I

Protection

IP: 65
IK: 09

Other operating numbers

Ambient temperature range: -13...86°F