Product data sheet


LUCAS VIII (1-ARMED) 9.858.5507.15 LEIPZIGER LEUCHTEN





High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately, inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



2 x Compact fluorescent lamp

26 W	LOR	80%
1800 lm	ULOR	4%
51 lm/W	Total flux	2867 lm
2899 K	Total power	56 W
90		
	1800 lm 51 lm/W 2899 K	1800 lmULOR51 lm/WTotal flux2899 KTotal power

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in

Electric System power: 56 W Protection IP: 55