


# Product data sheet

M26L - SPY 39 WALLWASH 927 MDL  
23433 9200  
DELTA LIGHT



Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M26L - SPY 39 WALLWASH 927 MDL, available in the colour(s): black, brushed alu, brushed anthracite, brushed copper, brushed gold, brushed old bronze, flemish bronze, flemish gold, gold coloured, white. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26L - PROFILE. This luminaire is equipped with LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: MDL = 1-10V or DALI or push button. Light distributor: lens.

## Light output 1



1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	753 lm	Total flux	548 lm
Luminous efficacy	126 lm/W	Total power	6 W
CCT	2700 K		
CRI	90		

## Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

## Shape and measurements

Length: 0.79 in  
Width: 6.69 in  
Height: 0.04 in

## Electric

System power: 6 W  
Appliance Class: II

## Protection

IP: 20  
Designation labels: CE