


Product data sheet

VERDA SYM WITH SHADE 740 CLO CG
305030-565
FAGERHULT



Installation Luminaire for assembly on a post, with post top Ø 60 mm. Connection Supplied with 5 m 3x1,5 mm² connection cable (H07RN-F). Design Body, heat sink and cover in cast aluminium. Diffuser of impact resistant UV-stabilised polycarbonate. Shade of enamelled aluminium, wet enamelled underside. Ballast integrated in the luminaire. Reflector Symmetrical reflector in acrylic (PMMA) or asymmetrical reflector in sheet metal. Light distribution Symmetrical or asymmetrical. Dimming CLO (Constant Light Output) maintains the correct light from the luminaire for the duration of its service life. Other options for light control available on request. For more information, see Light control. Standard Colour Anthracite grey (Gris 900 Sablé). Miscellaneous Projected area: from the side 0.105 m², from above 0.058 m². Luminaire weight: 6.3 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31 W	CRI	70
Total flux	2960 lm	LOR	100%
Luminous efficacy	95 lm/W	ULOR	7%
		Total power	31 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 22.64 in
Width: 22.81 in
Height: 21.20 in

Adjustability

Fixed

Electric

System power: 31 W

Protection

IP: 66