


Product data sheet

FLAT BASIC
211394.002.1
RZB




IP
43

IK
02

Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Diffuser fastening: spring system. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for Ceiling mounting, Wall (surface). Colour: pure white (RAL 9010) Diameter: 370 mm Height: 118 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 11 W Rated luminous flux: 1250 lm Beam angle Down: 117° Luminous efficiency: 114 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 43

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11 W	CRI	80
Total flux	1250 lm	LOR	74%
Luminous efficacy	114 lm/W	ULOR	20%
		Total power	11 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.65 in
Diameter: 14.57 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 11 W

Protection

IP: 43
IK: 02