Product data sheet


ZAAB 2 FLOODLIGHTS, PROJECTORS AND COLUMN PROJECTORS
ZA-20001-W-8030
LIGMAN



IP 66 IK 07


- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	40 W	CRI	80
Total flux	4201 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	50%
		Total power	40 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	40 W	CRI	80
Total flux	4201 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	50%
		Total power	40 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	40 W	CRI	80
Total flux	4201 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	50%
		Total power	40 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 18.39 in
Width: 5.91 in
Height: 59.06 in
Weight: 36.8 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 120 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 07
Surface temperature: 40°C