Product data sheet

131 LED COMPACT LIGHT FITTING 131 L13 (13101 0004)

SCHUCH










LED compact light fitting, 13 W, 1370 lm, 105 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI≥ 80, Ta -20 °C/+30 °C, L80>50000 h (@ Ta max), Diffuser PC satined, Closure Stainless steel (1.4301), Housing Plastic (PC), Colour white, for food areas. Small high impact resistant LED damp-proof light fitting with PC housing, frosted PC diffuser, with multiple hinge at one side, captive screws for closing the light fitting and silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 338,00 mm, Width/Diameter 120,00 mm, Height 90,00 mm, Net weight 0,50 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1370 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	7%
		Total power	13 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 13.31 in Width: 4.72 in Height: 3.54 in

Adjustability

Fixed

Electric

System power: 13 W Appliance Class: I

Protection

IP: 65 IK: 08

Designation labels: CE