Product data sheet


ECLDISPLAYCRMX_BLACK
ECLDISPLAYCRMXVW_2800K_8DEG
PROLIGHTS



IP 20 IK 08

The EclDisplay CRMX series presents an innovative and versatile range of LED spotlights, designed for use in galleries, commercial spaces, and other public venues. These advanced fixtures are distinguished by their refined design and multiple control options, including both wired and wireless protocols. They are adaptable to a variety of applications, thanks to the availability of different sources and optics. Each EclDisplay CRMX unit can be programmed and controlled via RDM, encompassing a comprehensive array of built-in input control protocols such as Wireless CRMX, DMX and local knob dimming. At the heart of the EclDisplay CRMX is a highly efficient White, high CRI LED source. This source is offered in multiple color temperature options: 35 W Variable White and 25 W 2.700K, 3,000 K, 4,000 K, and 5,600 K. The fixture's versatility is further enhanced by an extensive range of optional accessories, including profile (zoom and static) or wash lenses and additional optical elements like louvres and snoots. This makes the EclDisplay CRMX not just a lighting fixture, but a comprehensive lighting solution adaptable to a multitude of environments and needs. Main features: Data control through wireless CRMX, RDM, DMX and local knob dimming High CRI White LED available in 35W Variable White and 25W 2.700K, 3.000 K, 4.000 K, 5.600 K Multiple lens options: Profile (zoom and static) or wash optics

Light output 1



1 x LED

Nominal lamp power	31.7 W	LOR	100%
Lamp flux	535 lm	Total flux	536 lm
Luminous efficacy	17 lm/W	Total power	31.7 W
CCT	2817 K		
CRI	96		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 31.7 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE