



Product data sheet

PRO-CEILING 15W, 240MM
4000112X
PROLUMIA




Light source: SMD LED's Color rendering index: Ra>80 Operating temperature: -10°C - +40°C Rated life hours: 35.000 - 50.000 LED driver(included): CE, TUV LED-current: 500mA Input: 220-240Vac, 50/60Hz Power Factor: >0.90 Beam angle: 110°


Light output 1



1 x LED			
Nominal lamp power	15 W	LOR	100%
Lamp flux	1110 lm	Total flux	1110 lm
Luminous efficacy	74 lm/W	Total power	15 W
CCT	2700 K		
CRI	80		



1 x LED			
Nominal lamp power	15 W	LOR	100%
Lamp flux	1280 lm	Total flux	1280 lm
Luminous efficacy	85 lm/W	Total power	15 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	15 W	LOR	100%
Lamp flux	1190 lm	Total flux	1190 lm
Luminous efficacy	79 lm/W	Total power	15 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 15 W
Appliance Class: I

Shape and measurements

Height: 1.54 in

Diameter: 9.45 in

Protection

IP: 40

IK: 08

Designation labels: CE